Use Case Description
Example Relationship Database

Use Case Name:	Record subscriber profile
Iteration:	Filled
Summary:	The user enters or changes information about subscriber profiles
Basic Course of Events:	1. The user indicates that information about subscriber profiles is to be entered 2. The system prompts the user for: a. identifying information for the record to be entered/altered i. last name (name pattern for matching) ii. first name (name pattern for matching) iii. organization (name pattern for matching) b. action to take with the specified information i. Display records matching the criteria provided ii. Exit the use case 3. The system: a. displays information from pre-existing records in the system that match the information provided by the user in step 2 i. last name ii. first name iii. organizations the person is associated with 1. organization name 2. start date of organizational association 3. end date of organization association iv. publication subscriptions 1. publication name 2. subscription start date 3. subscription end date b. allows the user to: i. select one of the existing records for modification ii. indicate that a new record is to be entered iii. indicate that a different set of identifying information should be entered iv. exit the use case 4. The system prompts the user for: a. Current employer (free text entry??) b. Memberships of note (possible multiple entries) i. Organization (pick list or similar, not free text entry) ii. Remarks about membership c. Interests (possible multiple entries) i. Interest code (pick list or similar, not free text entry) The system also prompts the user to indicate what action to take with the information displayed/altered by the user: d. delete the displayed record from the system e. save record to system f. start anew for this record, discard changes already entered g. select a different record for modification, discard changes already entered 5. If the user has selected "save" in step 4, the system displays the information entered and prompts the user to indicate when they are finished viewing that information 6. The system returns the user to step 2
Alternative Paths:	1. At step 3, if the user selects "different set of identifying information", the system returns the user to step 2 2. At step 4, if the user selects "start anew", the system returns them to step 4, displaying the information originally present on the record before step 4, or to a blank screen in the case where a new record is being entered.

	3. At step 4, if the user selects "select a different record", the system discards any changes made by user and returns the user to step 2
Exception Paths:	1. At step 3, if no records matching the information provided by the user at step 2 are pre-existing, the user is still presented with the standard "step 3" display, but with a clear indication that no matching records were found.
Extension Points:	1.
Trigger:	1.
Assumptions:	1. The user has appropriate privileges for working with subscriber profiles information 2. Any classification codes, etc. to be applied to this record have already been entered into the system. 3. A "person" record for the individual being profiled is already entered in the system at the start of the use case.
Preconditions:	1.
Postconditions:	1. Information modifications entered by the user are appropriately stored in the system.
Related Business Rules:	
Author:	L.Bednar
Date:	Facade 7/29/2003; Filled 8/14/2003;

Notes

1. Extensions to other use cases may be desirable: (record membership definition, record interest definition).
2.

Information Item Descriptions

Use Case Name – A very short phrase describing the interaction of an actor (person, program, system, etc) with the system. Should begin with an active verb.
Iteration – Relates to the four stages through which a use case typically progresses

- façade – use cases entered primarily with summary information as "placeholders", with no strongly focused cross-checks or similar analysis completed
- filled – preliminary description completed, some cross-checking with other described use cases to eliminate duplicates, etc.
- focused – use cases analyzed, prioritized to differentiate essential from nonessential user interactions with the system, common elements identified
- finished. – user interface requirements and nonfunctional requirements are added, and use cases documentation is packaged for the system design effort

Summary – A short paragraph (1-2 sentences) explaining the interaction.
Basic Course of Events – A numbered outline of the usual course of the interaction. A "normal" interaction without errors, malfunctions or mishaps should be represented. If several different courses are possible, the most commonly occurring should be described.
Alternative Paths – Outlines of less common courses of interaction. These should represent "normal" interactions without errors, malfunctions, or mishaps.
Exception Paths - Outline of alternative courses of interactions in case of errors, malfunctions, or mishaps.
Extension Points – Shows the steps in a related use case that includes the use of the interaction described here.
Trigger – Description of the event or circumstance that causes the start of the use.
Assumptions – Description of any conditions assumed to be true, but which might not be true.
Preconditions – List of things that must be true before this interaction can occur.
Postconditions – List of things that are expected to be true after the interaction.
Related Business Rules – Business rules are the written and unwritten rules that dictate how a company runs its business. This section documents or refers to business rules that relate to this interaction.
Author – The name of the individual entering information into the use case description.
Date – The date of modification for the use case description.